

Australian Monitor

AMC+Mix

The Australian Monitor AMC+MIX brings the front end features of our AMC+ Series mixer into a simple and affordable mixer solution. When reliability is everything, but the more elaborate features of the Australian Monitor MX Series Mixers are not required, the AMC+MIX is the perfect choice.

The Australian Monitor AMC+MIX is a 1RU Mixer that features four universal mic/line inputs with phantom power. Master volume and overall treble and bass controls are provided, along with vox triggered muting (defeatable) giving channel one priority over channels two, three and four. There is also a facility to add an optional on-board tone generator card.

The Australian Monitor AMC+MIX gives the contractor a low cost alternative in price sensitive applications that still require reliability and a high level of sound reproduction.



Features

- 4 mic/line input mono mixer
- Master Volume, overall Treble and Bass controls
- 1 RU
- Optional Tone Generator
- On board priority vox muting
- 12VDC Phantom Power

Specifications

The mixer shall be 1RU in size with four universal XLR mic/dual RCA line level inputs. Channel one shall have priority over channels two, three and four. This can be internally defeated if required. The mixer shall have 12VDC phantom power, master volume treble and bass controls and feature a balanced XLR line level output as well as a dual RCA record level output. There shall also be facility for the mixer to accept a tone generation module (ATC5488).

The mixer shall be an Australian Monitor AMC+MIX.



AMC+Mix

Frequency Response		20Hz - 20kHz (+0,-3dB)
Total Harmonic Distortion		< 0.5% @ 1kHz
Signal To Noise Ratio		> 84dB (all pots at centre position)
Crosstalk		> 60dB
Tone Controls	Bass @ 100Hz	+/- 12dB
	Treble @ 10kHz	+/- 9dB
Sensitivity		Mic Sens 0.7mV, -61dBu Imp 1k3ohm Line Sens RCA 500mV, -4dBu Imp >100kohm
Max Level in		XLR mic -20dBu RCA >30dBu
Max Level out		+14dBu
Outputs	Master out	Nominal Level 0dBu into 1kohm Imp 100ohm
	Mono Rec out	Nom -16dB into 10kohm Imp 10kohm
Power Input		20V AC via 2.1mm x 5.5mm barrel socket
Power Consumption (max)		7 VA
Dimensions (H x W x D)		44 x 482 x 191.5mm (1.75" x 19" x 7.54")
Shipping Dimensions (H x W x D)		90 x 505 x 270mm (3.5" x 19.9" x 10.6")
Weight	Net	2.5kg (5.5lb)
	Shipping	3.5kg (7.7lb)

ENGINEERED BY AUSTRALIAN MONITOR

Address: 1 Clyde Street, Silverwater, Sydney NSW 2128 Australia. Private Bag 149, Silverwater NSW 1811 ABN 35 007 573 417

Website: www.australianmonitor.com.au International enquiries email: international@australianmonitor.com.au

DISTRIBUTED IN AUSTRALIA AND NEW ZEALAND BY HILLS SVL www.hillssvl.com.au

NSW P: 02 9647 1411 QLD P: 07 3852 1312 ACT P: 02 6260 4544 WA P: 08 9204 0200 VIC P: 03 9890 7477 SA P: 08 8408 8300 NZ P: 09 415 9426
E: nsw@hillssvl.com.au E: qld@hillssvl.com.au E: act@hillssvl.com.au E: wa@hillssvl.com.au E: vic@hillssvl.com.au E: sa@hillssvl.com.au E: sales@hillssvl.co.nz

